

ZEP SCREEN CLEAN - EUROPEAN AERO DZ OBS

Version 2.0

Revision Date 04/27/2018

Print Date 05/12/2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP SCREEN CLEAN - EUROPEAN AERO DZ OBS

Material number : 00000000000874910

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE
Emerson, GA 30137

Telephone : 404-352-1680

Emergency telephone numbers**For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation
Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616**Recommended use of the chemical and restrictions on use**

Recommended use : Carpet Care

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	colourless
Odour	characteristic

GHS ClassificationFlammable aerosols : Category 2
Gases under pressure : Liquefied gas
Eye irritation : Category 2A
Reproductive toxicity : Category 1B**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H223 Flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H360 May damage fertility or the unborn child.Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.

ZEP SCREEN CLEAN - EUROPEAN AERO DZ OBS

Version 2.0

Revision Date 04/27/2018

Print Date 05/12/2018

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
2-butoxyethanol	111-76-2	>= 5 - < 10
butane	106-97-8	>= 3 - < 5
acetone	67-64-1	>= 3 - < 5
propane	74-98-6	>= 1 - < 3
sodium borate, decahydrate	1303-96-4	>= 0.1 - < 1
sodium nitrite	7632-00-0	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
Consult a physician after significant exposure.

In case of skin contact : If skin irritation persists, call a physician.

ZEP SCREEN CLEAN - EUROPEAN AERO DZ OBS

Version 2.0

Revision Date 04/27/2018

Print Date 05/12/2018

- Wash off immediately with plenty of water for at least 15 minutes.
If on clothes, remove clothes.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
Rinse immediately with plenty of water for at least 15 minutes.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.
Effects are dependent on exposure (dose, concentration, contact time).
Symptoms may include irritation, redness, pain, and rash.
Chronic effects are delayed and symptoms may not be observed during an exposure.
Causes serious eye irritation.
May damage fertility or the unborn child.
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Water spray jet
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Smoke
- Specific extinguishing methods :

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

ZEP SCREEN CLEAN - EUROPEAN AERO DZ OBS

Version 2.0

Revision Date 04/27/2018

Print Date 05/12/2018

For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Do not breathe vapours or spray mist.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Always replace cap after use.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Observe label precautions.
Keep in a dry, cool and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Store and keep away from, oxidizing agents and acids.

ZEP SCREEN CLEAN - EUROPEAN AERO DZ OBS

Version 2.0

Revision Date 04/27/2018

Print Date 05/12/2018

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m ³	NIOSH REL
		TWA	50 ppm 240 mg/m ³	OSHA Z-1
		TWA	25 ppm 120 mg/m ³	OSHA P0
		PEL	20 ppm 97 mg/m ³	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m ³	NIOSH REL
		TWA	800 ppm 1,900 mg/m ³	OSHA P0
		PEL	800 ppm 1,900 mg/m ³	CAL PEL
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m ³	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m ³	OSHA Z-1
		TWA	750 ppm 1,800 mg/m ³	OSHA P0
		STEL	1,000 ppm 2,400 mg/m ³	OSHA P0
		STEL	750 ppm 1,780 mg/m ³	CAL PEL
		C	3,000 ppm	CAL PEL
propane	74-98-6	PEL	500 ppm 1,200 mg/m ³	CAL PEL
		TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m ³	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m ³	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m ³	OSHA P0
		PEL	1,000 ppm 1,800 mg/m ³	CAL PEL
sodium borate, decahydrate	1303-96-4	TWA	5 mg/m ³	NIOSH REL
		TWA	10 mg/m ³	OSHA P0
		PEL	5 mg/m ³	CAL PEL

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-BUTOXYETHANOL	111-76-2	Butoxyacetic	Urine	End of	200.mg/g	ACGIH BEI

ZEP SCREEN CLEAN - EUROPEAN AERO DZ OBS

Version 2.0

Revision Date 04/27/2018

Print Date 05/12/2018

		acid (BAA)		shift (As soon as possible after exposure ceases)	Creatinine	
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection
Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.
Safety glasses

Skin and body protection

: Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : colourless

Odour : characteristic

Odour Threshold : No data available

pH : 9 - 10

Melting point/freezing point : No data available

Boiling point : 43.3 °C

Flash point : 43.3 °C

ZEP SCREEN CLEAN - EUROPEAN AERO DZ OBS

Version 2.0

Revision Date 04/27/2018

Print Date 05/12/2018

Method: TCC

Evaporation rate	: 1
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: not determined
Relative vapour density	: No data available
Density	: 0.9922 g/cm ³
Solubility(ies)	
Water solubility	: soluble in hot water, soluble in cold water
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Acids Oxidizing agents
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION**Potential Health Effects**

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed. Effects are dependent on exposure (dose, concentration,

ZEP SCREEN CLEAN - EUROPEAN AERO DZ OBS

Version 2.0

Revision Date 04/27/2018

Print Date 05/12/2018

contact time).

Symptoms may include irritation, redness, pain, and rash.
Chronic effects are delayed and symptoms may not be observed during an exposure.

Carcinogenicity:

IARC	Group 2A: Probably carcinogenic to humans
ACGIH	sodium nitrite 7632-00-0 Confirmed animal carcinogen with unknown relevance to humans
OSHA	2-butoxyethanol 111-76-2 No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity**Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 15.02 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:**2-butoxyethanol:**

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l
Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

ZEP SCREEN CLEAN - EUROPEAN AERO DZ OBS

Version 2.0

Revision Date 04/27/2018

Print Date 05/12/2018

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

ZEP SCREEN CLEAN - EUROPEAN AERO DZ OBS

Version 2.0

Revision Date 04/27/2018

Print Date 05/12/2018

Components:**butane :**
 Partition coefficient: n- : Pow: 2.89
 octanol/water
Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: No data available

SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

Waste from residues	: Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations. The product should not be allowed to enter drains, water courses or the soil.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1,

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1,

Transportation Regulation: IATA (Passenger Air):

ZEP SCREEN CLEAN - EUROPEAN AERO DZ OBS

Version 2.0

Revision Date 04/27/2018

Print Date 05/12/2018

This material is not classified.

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

sodium nitrite 7632-00-0

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium nitrite	7632-00-0	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Gases under pressure
Serious eye damage or eye irritation
Reproductive toxicity

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

2-butoxyethanol	111-76-2	9.9865 %
-----------------	----------	----------

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

ZEP SCREEN CLEAN - EUROPEAN AERO DZ OBS

Version 2.0

Revision Date 04/27/2018

Print Date 05/12/2018

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARD	3

0 = not significant, 1 =Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms :



Signal word :

Danger:

Hazard statements :

Flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May damage fertility or the unborn child.

Precautionary statements :

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

ZEP SCREEN CLEAN - EUROPEAN AERO DZ OBS

Version 2.0

Revision Date 04/27/2018

Print Date 05/12/2018

Version:	2.0
Revision Date:	04/27/2018
Print Date:	05/12/2018

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.