



Plan View  
Scale 1" = 20'

### LUMINAIRE SCHEDULE

Symbol	Label	Qty	Catalog Number	Description	Lamp	File	Lumens	LLF	Watts
■	A	15	VANLED10N	CAST METAL HOUSING, EXTRUDED FINNED METAL HEAT SINK, 1 WHITE CIRCUIT BOARD WITH 48 LEDs, MOLDED PLASTIC REFLECTOR WITH SEMI-SPECULAR FINISH, CLEAR FROSTED HOLOGRAPHIC PLASTIC DROP LENS IN CAST METAL FRAME. LENS FROSTED SIDE IN.	FORTY EIGHT LIGHT EMITTING DIODES (LEDs), VERTICAL BASE-UP POSITION. VANLED20Y. ACTUAL PERFORMANCE MAY VARY. Gymnasium, Industrial, Institutional, Manufacturing, Recreation Site, Sports, Ambient, Low Bay, Damp Location, Wet Location	VANLED10N.i.e.s	1708	1.00	13.5
■	C	26	BRISK8N	CAST BROWN PAINTED METAL HOUSING, FORMED SPECULAR PAINTED REFLECTOR, 1 WHITE CIRCUIT BOARD WITH 16 LEDs, MOLDED FROSTED PLASTIC LENS.	FIFTEEN WHITE LIGHT EMITTING DIODES (LEDs), TILTED 30-DEGREE FROM VERTICAL BASE-UP POSITION. BRISK8N. ACTUAL PERFORMANCE MAY VARY. Healthcare, Hospitality, Hotel, Dock, Garage, Institutional, Manufacturing, Recreation, Sidewalk, Site, Parks, Pathway, Wet Location	BRISK8N_PCU.i.e.s	970	1.00	8.87
■	P2H	2	DSX0 LED 20C 700 40K T2M MVOLT HS	DSX0 LED WITH 20 LEDs @700 mA, 4000K, Type 2 Medium Optics with HOUSE-SIDE SHIELD	LED	DSX0_LED_20 C_700_40K_L2 M_MVOLT_HS.i.e.s	4755	1.00	45
■	PLC	1	DSX0 LED 20C 700 40K LCCO MVOLT	DSX0 LED WITH 20 LEDs @700 mA, 4000K, LEFT CORNER CUTOFF OPTIC	LED	DSX0_LED_20 C_700_40K_L CCO_MVOLT.i.e.s	4078	1.00	45
■	PRC	1	DSX0 LED 20C 700 30K RCCO MVOLT	DSX0 LED WITH 20 LEDs @700 mA, 3000K, RIGHT CORNER CUTOFF OPTIC	LED	DSX0_LED_20 C_700_30K_R CCO_MVOLT.i.e.s	3798	1.00	45

### STATISTICS

Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min
Calc Zone #1	+	1.2 fc	14.1 fc	0.0 fc	N / A	N / A
Parking Area	X	3.0 fc	14.1 fc	0.3 fc	47.0:1	10.0:1

### NOTES

- VALUES SHOWN ARE INITIAL FOOTCANDLES BASED UPON MANUFACTURER'S TEST DATA.
- THIS STUDY DOES NOT MODEL LANDSCAPING AND SHADOWING CAUSED BY VEGETATION.

### Designer

KLP

### Date

Sep 11 2017

### Scale

AS SHOWN

### Drawing No.